

Provisional Specifications - Europe





3 cabins 2 heads version:



3 cabins 3 heads - Skipper's cabin version:



GENERAL SPECIFICATIONS * _____

L.O.AHull length	17,16m 15,98m	56'4'' 52'5''
• L.W.L.	15,40m	50'6''
Beam	5,00m	16'5"
 Standard draft (T-keel) 	2,50m	8'2"
 Standard ballast weight (Cast iron) 	4 500kg	9,918 lbs
Performance draft (T-keel)	3,00m	9'10"
 Ballast weight performance (Cast iron/ 		
Lead)	4 510kg	9,940 lbs
 Air draft (excluding antennae) 	25,80m	85'
 Performance air draught (excluding 		
antennae)	26,80m	88'
Light displacement	15 500kg	34,162 lbs
Fuel capacity (standard)	400L	106 US Gal
 Fresh water capacity (standard) 	720L	190 US Gal
Engine power:		
 Sail drive (standard) 	80 HP	80 HP
 Propeller shaft (Option) 	110 HP	110 HP

ARCHITECTS / DESIGNERS _____

- Naval Architect: BISCONTINI YACHT DESIGN
- Outside & interior design: LORENZO ARGENTO

EC CERTIFICATION * ____

- Category A 10 people
 Category B 12 people
 Category C 14 people

STANDARD SAILS DIMENSIONS * _____

CLASSICAL MAST ALUMINIUM

 Mainsail Furling genoa (105 %) Code 0 Asymmetric spinnaker I J P 	87,00m² 78,90m² 179,00m² 254,00m² 21,95m 6,40m 22,00m	936 sq/ft 849 sq/ft 1,926 sq/ft 2,730 sq/ft 72' 21' 72'2"
• P	22,00m	72'2''
• E	6,80m	22'4''

CARBON CLASSICAL MAST (+ 1m / 3'3")

 Performance version mainsail 	91,00m²	979 sq/ft
 Furling genoa (105 %) 	82,00m ²	882 sq/ft
• Code 0	185,00m ²	1,990 sq/ft
 Asymmetric spinnaker 	265,00m ²	2,850 sq/ft
•1	22,90m	75 [°] 2"
• J	6,40m	21'
• P	23,00m	<i>75'6''</i>
• E	6,80m	22'4"

^{*} Provisional specifications, boat in process of certification.



Provisional Specifications - Europe

STANDARD EQUIPMENT

CONSTRUCTION

- Design in accordance with European Directive requirements and according to CE certification
- · Balsa sandwich infusion hull
- Vacuum infused structural inner liner (Fabrics resin) bonded to the hull
- Deck in glass fibre/balsa wood sandwich infusion, with non-slip "diamond point" surface
- Cast iron keel attached with bolts and bonded stainless steel backplate
- · Twin rudders hung with stainless steel stock
- · White coloured hull Aluminium grey hull decoration
- · 8 Hull portholes

DECK EQUIPMENT_____

RIGGING

- · Depending on version:
- Black lacquered aluminium classical mast tapered, deck stepped,
- 3 Aft swept spreaders,

Dyform Rigging,

Dyform backstay crowfoot with manual hydraulic piston to starboard (hydraulic unit optional),

Harken fixed blocks at foot of mast,

Harken Switch mainsail track (without traveller)

- **Performance carbon classical mast** tapered, deck-stepped (+ 1m / 3'3", Weight saving: 100kg / 220 lbs)

3 Aft swept spreaders

ROD Rigging

Textile backstay crow's foot with manual hydraulic piston to starboard

Harken fixed blocks at foot of mast

Harken Switch mainsail track (without traveller)

- Lacquered aluminium Racing boom with LED lighting (warm white)
- Black Racing lacquered aluminium rigid kicking strap with Dyneema tackle and friction rings (hydraulic available as an option)
- Genoa track on the roof with traveller and hauling line controlled from the cockpit
- · Manual Genoa furler below deck
- 1 mainsail attachment point at bottom of cockpit with 1 stand-up block
- German system (Two-way mainsheet at the helm station)
- All lines brought back to the helm stations (except boom topping lift)
- Dyneema Complete running rigging:
 - Mainsheet halyard sheave block,
 - Genoa halyard,
 - Boom uphaul (polyester) with cleat on mast,
 - Mainsheet,
 - 2 Genoa sheets,
 - 2 Automatic reefing system
- 7 halyard clutches to port, 4 to starboard
- HARKEN Black Magic blocks
- 2 Spinnaker sheet chain plates/code 0
- Running rigging hidden
- · 2 Flag halyards
- Windex Windvane

WINCHES

- 1 Manual self-tailing winch to starboard (H50.2 STP)
- 1 Electric self-tailing winch to port (H50.2 STP)
- 2 Manual Genoa winches (H70.2 STP)
- · 2 Aluminium Speed Grip winch handles
- · Stowage of which handles in dedicated space in rope bags

SAILS

Boast supplied without sail

MOORING LINES - MOORING

- Polyester bowsprit with integrated anchoring gear and bobstay with spinnaker chainplate (for Code 0 and asymmetric spinnaker)
- · Self-draining chain locker, Clench bolt, Piston-driven cover
- Single roller stainless steel bow fitting
- 12 V 1 500 W vertical electrical windlass Remote control in mooring locker
- 6 Black anodised aluminium mooring cleats (Length: 0,14m / 15³⁴)
- Stainless steel chafing plate

SAIL LOCKER

Access through T70 deck hatch, Passage width: 0,65 x 0,65m / 2'2" x 2'2"

- · Stainless steel ladder
- · Shelving and stowage trays
- LED lighting
- 1 230V socket

SAFETY ON DECK

- 1 Black lacquered stainless steel open pulpit
- · 2 Black lacquered stainless steel aft pulpits with integrated fairlead
- 1 Black lacquered stainless steel central aft pulpit (Height: 960mm / 3'2")
- · 2 Black lacquered stainless steel handrails on the roof
- 1 Lifebuoy support bracket on aft pulpit
- Wooden flagstaff (1 m/3'3") with integrated support on deck
- Dual textile lifelines and black lacquered stainless steel stanchions (Height: 620mm / 2) - Side boarding gate on either side
- · Emergency ladder on pushpit

COCKPIT

- Self-draining cockpit
- Teck decking
- 2 Sail lockers below cockpit seating
- 2 Stowage lockers behind the cockpit with stainless steel support for the fenders (650 x 390mm / 2'2" x 1'3")
- 1 Access hatch to tender garage
- 1 Integrated housing in catwalks for diesel deck filler and shore power socket
- 3 water deck fillers at the forward end of the roof on the catwalks
- 1 Gas locker on forward deck next to anchor chain locker, space of 2 bottles
- Natural solid wood slatted cockpit benches
- · Side helmsman's seat, wooden slats
- Foldaway helmsman foot chock
- · 2 Steering wheel consoles:
- Black composite helm (diameter 1 100 mm/3'7") fixed on white lacquered aluminium pedestal
- Steering gear at the helm station
- Stainless steel steering chain transmission system
- Black lacquered stainless steel hand rail
- 1 Emergency tiller
- 1 Steering compass on port console
- Engine throttle and control panel on starboard
- 1 Cockpit shower with mixer tap in the tender garage
- 1 PPMA folding companionway door in the bottom of the cockpit -Sliding hatch made of PMMA
- Liferaft locker in front of the companionway (Space for 12 place liferaft: 0,96m x 0,59m x 0,40m / 3'2" x 1'11" x 1'4")
- · Courtesy lighting (7 LED lighting points, warm white lighting)



Provisional Specifications - Europe

SWIM PLATFORM / STERN DECK

- Fully opening transom, convertible to bathing platform (2,61m x 0,93m / 8'7" x 3'1")
- · 3 Folding access steps to the cockpit to starboard
- Electrically controlled opening on console
- · Natural solid wood decking on swim platform
- 1 Stainless steel, removable bathing ladder with dedicated stowage in the cockpit

TENDER GARAGE

Accessible from the platform and from the cockpit Can be used to house a Highfield UL240 type tender (2,48m x 1,69m x 0,80m / 8'2" x 5'7" x 2'7")

• 1 Touch-operated ceiling LEDs

INTERIOR

- Alpi teak woodwork and white lacquered wood on base units and bulkheads
- Alpikord teak flooring
- Lounge Falcon 162 fabric internal upholstery
- Mattresses in the cabins (HR foam 35 kg/m³, thickness 120 mm/5")
- Beige padded ceilings (and Macadamia in the central part of the saloon)

Standard version: 3 cabins + 2 heads



COMPANIONWAY

Headroom: 2,00m / 6'7"

- Saloon companionway with 5 suspended Alpikord teak non-slip steps, LED lighting below each step
- · 2 Valencia Meteor encased stainless steel handrails

SALOON

Headroom: 2,00 - 1,97m / 6'7" / 6'6"

Starboard saloon:

- Very comfortable Lounge type L-shaped sofa:
- seats with HR26 and HR30 foam
- softness thanks to the finish with hollow fibres + padding
- Coffee table, wooden top with moulded beading, access to bottle rack opposite the seat
- · Storage under bench seats
- 1 Electrical panel to starboard incorporated into a piece of furniture for access to electrical connections
- · 2 Portholes with integrated blind
- 2 Coachroof windows including opening porthole with mosquito net
- 2 Opening deck hatches with mosquito screen/blinds
- Indirect LED lighting below the soft and the upper part of the portholes
- 1 Adjustable reading light
- 1 USB port dual port
- 1 230V socket
- Audio:
- Fusion RA70N entertainment system
- 2 Interior loudspeakers
- 2 Waterproof exterior speakers

Port saloon:

- · Wooden table with integrated sliding extension leaf
- Face-to-face bench seats with extension (can seat up to 6 diners)
- · 2 Portholes with integrated blind
- Storage under bench seats
- 1 Deep storage unit against bulkhead + 1 Valet tray (unless air conditioning option chosen)
- Indirect LED lighting on the upper part of the portholes
- 1 230V socket close to forward bulkhead
- Pillar with beige cover

GALLEY - PORT

Headroom: 2,01m / 6'7"

- · C-shaped galley
- Corian Glacier White work top with moulded teak beading
- 1 1 rectangular stainless steel sink 1 Mixer tap with hot/cold water under pressure
- 1 Gas cooker 2 burners Stainless steel oven on gimbal (17L) -Stainless steel protection handrail - Stowage below the oven with drop-down door
- 1 Stowage on work top with top opening (Space for optional 36 L stainless steel cool box)
- 12 V 174 L fridge with integrated 16 L freezer (-18 °C), 1 Front opening door
- · Fitted lockers and closed shelving
- 1 Bin (20L)
- 1 Base unit: 1 drawer on the side, 2 doors, 1 shelf
- · 2 Opening portholes with mosquito nets

OWNER'S CABIN

Headroom: 2,01 - 1,96m / 6'7" - 6'5"

- Central double bed (2,00m x 1,60m 1,15m / 6'9" x 5'3" 3'9") with Lounge Greige 160 fabric padded bedstead
- · 1 Bed access sideboard
- 1 Chair on each side of bed with Lounge Falcon 162 fabric
- · 2 Shoe stowage beneath the bed
- · 2 Hanger closets, with incorporated LED lighting
- 1 Central full-height unit with LED lighting: 4 drawers at the bottom,
 1 door with 4 shelves, mirror inside the door
- · 2 Night tables
- 2 Flexible and adjustable bedside lamps
- 1 T70 flush deck hatch with blind/mosquito net
- · 2 Portholes with rigid sliding blind
- 1 230 V power socket on each side of the bed
- 1 dual port USB outlet on each side of the bed
- · LED indirect lighting + Spot lighting

2 PRIVATE HEADS

To starboard:

Headroom: 1,92m / 6'4"

- 1 Manual toilet
- 1 80 L / 13 US Gal rigid holding tank
- · Work top in Corian Glacier White
- 1 Integrated polyester basin Mixer tap
- 1 Cabinet Mirror
- · Toilet accessories
- 1 Deck hatch with mosquito screen/blind
- LED indirect lighting + Spot lighting

to port:

Headroom: 1,97m / 6'6"

- Shower with seat and wooden shower base
- 2 Open stowage trays
- · 1 Deck hatch with mosquito screen/blind
- · LED indirect lighting



Provisional Specifications - Europe

PORT AFT CABIN

Headroom: 1,92m / 6'4"

- 1 Double bed (2,04m x 1,40m / 6'8" x 4'7")
- · 1 Hanging locker, 1 Cupboard with shelves, with incorporated LED
- · 2 Lockers with top opening along the hull
- · 1 Bed access sideboard
- 1 Drawer under the bed
- 1 Large stowage under the bed, top opening (location for air conditioning option)
- 1 Flexible, swivelling reading light at bedhead
- 1 Flexible and adjustable reading light on the hanging locker
- 1 USB port dual port
- 1 230V socket
- · 1 Porthole with rigid sliding blind
- 1 Opening window with below cockpit seat with pleated blind
- 2 Opening windows on coaming with pleated blind (1 with the 3 heads version)

STARBOARD AFT CABIN

Headroom: 1,92m / 6'4"

- 1 Double bed (2,04m x 1,40m / 6'8" x 4'7")
- · 1 Hanging locker, 2 lockers with top opening along the hull
- · 1 Bed access sideboard
- 1 Drawer under the bed
- 1 Large stowage under the bed, top opening (location for air conditioning option)
- 1 Flexible, swivelling reading light at bedhead
- 1 Flexible and adjustable reading light on the hanging locker
- 1 USB socket
- 1 230V socket
- · 1 Porthole with rigid sliding blind
- · 2 Opening windows with below cockpit seat with pleated blind
- · 1 Opening window on coaming with pleated blind

AFT STARBOARD HEAD COMPARTMENT

Headroom: 1,95m / 6'5"

Access from the saloon or the starboard aft cabin

- Separate shower 1 Mixer tap White polyester shower base
- · Corian Glacier White work top with self-draining storage
- · 1 Manual toilet
- 1 80 L / 21 US Gal rigid holding tank
- 1 Washbasin 1 Mixer tap1 Cabinet + Storage space under the basin
- · Toilet accessories
- 1 Opening porthole on coaming in side window, opaque film, mosquito screen

3 cabins 3 heads version (Option)



This head stands between the galley and the after port cabin: single hanging locker and one opening porthole in the aft cabin

AFT PORT HEAD COMPARTMENT

Headroom: 2,03m / 6'8"

Access by the aft starboard cabin

- · Polyester work top with integrated basin 1 Mixer tap 1 Shower -White polyester shower base
- 1 Manual toilet
- 1 50 L / 13 US Gal rigid holding tank
- 1 Bathroom cabinet 2 doors
- 1 Mirror above the washbasin
- Toilet accessories
- · 1 Opening porthole on coaming in side window, opaque film, mosquito screen
- 1 Fixed window on coaming, opaque film



Provisional Specifications - Europe

ENGINE

- · Engine Yanmar Diesel:
- 80 HP/80 HP, Sail Drive, Common Rail (standard)
- 110 HP/110 HP, Propeller shaft, Common Rail (Option)
- Engine control at the starboard helm station Control panel
- Engine compartment:
 - Soundproofing foam
 - Ventilation: 2 air intakes and 1 forced air outlets
 - Automatic LED lighting
- · Engine data visible on the B&G screen
- 1 Alternator (12V / 125 Ah)
- 2 Rotomoulded diesel tank 2 x 200 L/2 x 53 US Gal (under aft berth port and starboard) - Electronic gauge - Low level alarm - 1 Deck filler
- Filters: Seawater Diesel Water separator
- · Foldaway three-blade propeller
- 1 Engine access through companionway (opening with 2 gas struts)
- · 2 Engine access through aft cabins

PLUMBING

- 1 Rotomoulded freshwater tank 380 L / 100 US Gal, under berth in forward cabin - 1 Deck filler
- 2 Rotomoulded diesel tank 2 x 150 L/2 x 40 US Gal, under saloon floor, port and starboard - 1 Deck filler
- · Pressurised electric water pump Expansion tank Inline filter
- 40 L / 11 US Gal Electric water heater (engine use)
- 1 Rigid black water holding tank for each WC
- Electrical shower drain pumps
- 1 Electric bilge pump
- 1 Manual bilge pump
- Transfer valves easily accessible from the companionway

GAS

- 1 Box for 2 gas bottles in the anchor locker (Diameter: 0,28m / 11"x Height: 0,45m / 1'6")
- · Regulator and safety tap
- Gas leak detector

ELECTRICITY

- 12 V electrical panel (Breaker, Voltmeter, Water gauge, Fuel gauge, Battery warning, Fuel warning, Water warning) + USB port dual port + Navicolor 3.5" screen
- Radio controlled wireless light switches (no battery) for lighting (excluding heads)
- Ship Control technology control numerous functions from the navigation screens (or from a tablet or smartphone using a dedicated app):
- Anchoring and masthead navigation lights
- Lighting of boom, spreaders (optional), underwater spotlights (optional)
- Courtesy light in cockpit
- Direct lighting
- Deck searchlight
- Inverter (Option)
- Fridge
- Water unit
- Bilge pumps
- Air conditioning (Option)
- Generator (Option)
- Audio
- Monitoring of tanks
- Battery monitoring
- 12V circuit
- 3 AGM service batteries (140 Ah)
- 1 AGM engine battery (100 Ah)
- · Battery cut-off switch easily accessible from the companionway
- 1 Battery charger (60 Ah)
- 1 Power distributor
- · 10 230V Sockets:
- 2 in the forward cabin
- 1 in the forward port head
- 1 in the aft cabins
- 1 in the saloon (Starboard)
- 1 at chart table
- 1 in galley
- 1 in the engine compartment
- 1 in the sail locker
- 6 Dual USB socket:
 - 2 in the forward cabin
 - 1 in the aft cabins
 - 1 on the electrical panel
 - 1 at chart table
- 1 Shore power socket 230 V
- LED lighting:
 - Overhead lights, with dimmer
- Reading lights
- Indirect lighting, with dimmer
- LED navigation lights:
 - 1 Masthead light
 - 1 Steaming light
 - 1 Anchor light on masthead
- Deck searchlight (Halogen)
- · Wire runs for option cables



Provisional Specifications - Europe

TRIM LEVEL & PACKS

TRIM LEVEL _____

	CONFORT	LUXE
Coastal B&G Pack	•	
1 Harken Performa H50.2 STPEH starboard electric manoeuvring winch (in lieu of standard)		
Windlass control in cockpit with chain counter		
Tilting transom remote control		
 Retractable bow thruster + 4 Dedicated batteries (50 Amps - 12V) + 1 Battery charger (30 Amps - 24V) 		
TECMA electric fresh water/sea water WC in the owner's head		
IBS sensor		
2 Additional 140 ampères service batteries		
Additional 40 ampères battery charger		•
Electrical engine control on the starboard console		
Yacht Case - Tableware		
Mosquito nets for opening portholes	•	•
Offshore B&G Pack		
 2 Teak cockpit tables with extensions on stainless steel pedestal and Charcoal Grey covers Outside cockpit upholstery, Sunbrella Terry beige seats and backrests (terrycloth), Filter foam 		•
80 mm/3" thickness (Density: 60F + 20S)		•
Spring mattress in the owner's cabin (thickness: 180mm / 7")		
Quiet Flush fresh water/seawater electric WC in the aft starboard head		•

ELECTRONICS PACKS: B&G _____

	COASTAL (included in the Confort trim level)	OFFSHORE (included in the Luxe trim level)
 Port and starboard helm stations: 1 12" Zeus³ wide wireless multi-function touchscreen (GPS, Chart plotter, Card reader - Navionics Silver cartography included) 	•	•
 H5000 unit: Aeriel Wind Sensor (pole 1 m/3'3"):Windvane, Anenometer Sensor (Log, Speedometer, Temperature) 		
• PC interface		•
 V90S VHF radio fixed to the chart table, AIS receiver function Protective covers for helm & consoles (Charcoal Grey) 	•	•
B&G H5000 autopilot with keyboard on port console	•	-
WR10 Wireless autopilot remote control		

PACK FASTNET (implies pack Offshore)

- 3 Mast foot repeaters (20 x 20)
- AIS NAIS 500
- H50 wireless VHF set



Provisional Specifications - Europe

RIGGING PACKS

MAINSAIL WINCH PACK (Compatible with the 2 masts)

- · Self-tailing HARKEN Performa (H50.2 STPEH) electric winch on polyester turret in centre of cockpit
- · Standard German System replaced by 1 Dyneema mainsheet

PACK DOWNWIND (Compatible with the 2 masts)

- · 2 Additional halvard clutches to starboard
- 2 HARKEN Black Magic blocks for spinnaker sheet/code 0
- 1 HARKEN Black Magic block for spinnaker tackline with return on dedicated cleat in cockpit
- 1 Dyneema sheaved halyard with block for spinnaker or code 0
- 1 Dyneema halyard for spinnaker
- 1 Spinnaker tackline with return on dedicated cleat in cockpit

STAYSAIL RIGGING PACK (Compatible with the 2 masts - Requires hydraulic unit option)

- 1 Clutch to starboard
- 1 Wichard double chainplate on forward deck for removable forestay
- · 1 Dyneema halyard sheave with block for staysail

SELF-TACKING RIGGING PACK (Compatible with all masts and all rigging packs)

- · Self-tacking jib hardware (sheet only)
- · 1 Self-tacking jib track with traveller
- · 1 Jib sheet clutch to starboard

CARBON MAST SAILS PACK

- Mainsail (91 m²/979 sa/ft) and Genoa (82 m²/882 sa/ft) North Sails NPL tour, dark grey
- · Charcoal Grey lazy bag + lazy jack

ALUMINIUM SAILS MAST PACK

- Mainsail (87 m²/936 sq/ft) and Genoa (82 m²/882 sq/ft) North Sails NPL tour, dark grey
- · Charcoal Grey lazy bag + lazy jack

MOORING PACK

- Delta stainless steel 32 kg/71 lbs anchor
 Chain (Diameter: 12mm / ¹/₂" Length: 40m / 131')
 Line (Diameter: 22mm / ⁷/₈" Length: 50m / 164')
- 6 Fenders:
- 6 Ferroers.
 4 XL (Diameter: 300mm / 12" Length: 0,88m / 2'11")
 2 L (Diameter: 250mm / 10" Length: 0,70m / 2'4")
 4 Moorings lines (Diameter: 18mm / ¹¹/₁₆" Length: 15m / 49'3")

MOORING PACK (inflatable)

- Delta stainless steel 32 kg/71 lbs anchor
- Chain (Diameter: 12mm / ¹/₂" Length: 40m / 131')
 Line (Diameter: 22mm / ⁷/₈" Length: 50m / 164')

- 6 Fenders (Diameter: 360mm / 1'2" Length: 1,20m / 2'11")
 4 Moorings lines (Diameter: 18mm / ¹¹/₁₆" Length: 15m / 49'3')



Provisional Specifications - Europe

OPTIONS

NAVIGATION ELECTRONICS: B&G _

- Chart table: 12" Zeus³ wide wireless multi-function touchscreen
- H50 wireless VHF set
- Forward Scan Sensor (Forward underwater vision)
- AIS NAIS 500

RIGGING - SAILS

- FurlerBoom V-shaped boom furler, black lacquered, epoxy glassfibre casing/carbon spindle (requires carbon mast version + hydraulic unit option), Integrated LED lighting for the cockpit area
- · Hydraulic unit (for carbon mast): Hydraulic textile backstay on piston + Hydraulic kicker tackle on unit (2 Functions / 2 speeds)
- Hydraulic unit (for aluminium mast): ROD rigging and hydraulic textile backstay on piston + Hydraulic kicker tackle on unit (2 Functions / 2 speeds)
- · Electric Genoa furler below deck
- Aluminium black lacquered canoe boom with hydraulic piston, Sparcraft (Requires hydraulic unit option), Integrated LED lighting for the cockpit area
- · Code 0 with North Sails NPL tour furler, laminated, dark grey for aluminium mast
- Code 0 for carbon mast

WINCHES

• 2 Electric Harken Performa genoa sheet winches (H70.2 STPEH)

HULL - DECK - COCKPIT

- · Blue grey or pearl grey gel-coat
- · Hull and deck paint
- Retractable capstan (Bow)
- Canopy with LED lighting, Strataglass windows, Charcoal Grey
- · Bimini with sunshade, Charcoal Grey
- · LED lighting of spreaders
- Sunshade on foredeck, Charcoal Grev
- · Retractable stern thruster
- Carbon or white composite helm
- Retractable NOMEN black anodised cleats (in lieu of standard)
- · Accommodation ladder
- · Outboard engine bracket
- Folding composite gangway (2,60m / 8'6")
- · Electric inflator/deflator for tender and fenders (portable, batterypowered)
- Shore fresh water supply
- Seawater/fresh water deck washing pump
- 3 Underwater lights (1 forward, 2 aft)
- 1,20 m/3'11" carbon flagstaff (in lieu of standard)

INTERIOR EQUIPMENT _____

LAYOUT VERSIONS

- · 3 cabins 2 heads version
- · 3 cabins 3 heads version
- · Skipper cabin replacing the sail locker of the foredeck: Access through T70 deck hatch, Stainless steel ladder, 1 Berth, Toilet, Washbasin, Shower, 1 USB port dual port

· Internal upholstery according to colour chart: Fabrics, Leather, Nubuck. Ultraleather

MULTIMEDIA

- Folding 32" LED TV, in the saloon
 TV LED 22", in the forward cabin
- · Hifi APOLLO + Bose 2.1 speakers, in the saloon (in lieu of standard)

DOMESTIC APPLIANCES

- · Dishwasher for 6 sets
- · Built-in 22 L grill and microwave combined oven
- · Wine cellar 23 bottles
- · 3 kg washer dryer
- 36 L cool box with access from the galley work top, stainless steel tank (temperature adjustable from +10 °C to -12 °C)

ON BOARD COMFORT EQUIPMENT

- · Spring mattress in the aft cabins (thickness: 160mm / 6")
- Generator (7,5 KVA, 230V, 50Hz)
- Watermaker (60 l/h / 16 US Gal/h)
- Air conditioning 44 000 BTU (+ Shore socket extension cord 15m / 49'3") - 32A
- Forced air heating fuel
- · Safe, in the forward cabin
- 12V / 230V inverter 2 000 VA
- · Electric battery switch (connected to the Ship Control, controls powering on or shut-off of batteries remotely)
- · Lithium battery replacing the AGM batteries Weight saving: Approximately 170 kg / 375 lbs (requires Confort trim level)
- Seawater electric pump, in gallev